





Irritrol's I-PRO[™] Series spray heads combine a pressure-activated wiper seal and advanced formula lubricant that virtually eliminates troublesome stick-ups. Add a unique tapered lip design that prevents debris from entering the body and you have a spray head with superior performance. It's rugged and reliable with a textured body style for a non-slip grip and even easier installation. I-PRO offers a 4", 6" and 12" replacement spray head that allows a complete retrofit without having to purchase the body – it even fits the Rain Bird[®] *1800[®]* Series body. Available in four pop-up heights with side inlet, pressure regulation and check valve options, the I-PRO Series fits most landscape applications.

*Rain Bird® and 1800® are trademarks of Rain Bird® Corporation.

-PRO[™] SERIES POP-UP SPRAYS

PRESSURE-ACTIVATED SEAL WITH LUBRICANT ADDITIVE

Cleans debris from stem, reduces flow-by during pop-up and prevents leaking between cap and body. Extra lubricant additive further eliminates stick-ups

PRE-INSTALLED IN-RISER PRESSURE REGULATOR (OPTIONAL) Maintains optimum nozzle performance at 30 psi and eliminates misting in varying pressure applications

PRE-INSTALLED CHECK VALVE (OPTIONAL)

Prevents low-head drainage, eliminating flood or erosion damage by keeping water in lateral pipes in elevation changes up to 14'

RETROFITTABLE RISER Fits Rain Bird 1800 Series body

STURDY AND ROBUST, TEXTURED BODY Provides for easy installation with a non-slip grip

SIDE AND BOTTOM INLETS ON 6" AND 12" MODELS (6" ALSO AVAILABLE IN NON-SIDE INLET) Reduces installation time

HEAVY-DUTY, STAINLESS STEEL RETRACTION SPRING Ensures positive pop-down

MALE-THREADED RISER

Compatible with any female-threaded nozzle in the industry

PRE-INSTALLED FLUSH PLUG

Makes system flushing a breeze and allows for easy nozzle installation

RATCHETING RISER

Easiest ratchet in the market, even while hands are wet, yet won't come out of adjustment!

RETROFITTABLE RISER FAMILY AVAILABLE






IRRITROL.COM

SPECIFICATIONS

- Inlet size: 1/2" female NPT threads
- Exposed diameter: 2 1/4"
- Body diameter: 1 ⁵/8"
- Body height:
- I-PRO300: 4 7/8"
- I-PRO400: 5 ³/4"
- I-PRO600: 9 ¹/4"
- I-PRO1200: 16"
- Side inlet: 4 ³/8" from center of side inlet to top of cap
- Recommended working pressure:
 - Standard: 20-50 psi (max 75 psi)
- CV: 25-50 psi (max 75 psi)
- PR: 30-70 psi (max 75 psi)
- Precipitation rate:
- Spacing: 4' 15'
- Flow-by: 0 at 10 psi or greater; .1 GPM otherwise
- Five-year warranty

SPECIFYING INFORMATION



MODELS

	<u>Model</u>	Description
	- I-PRO300	3″ Pop-Up
	I-PRO400	4" Pop-Up
	I-PRO400-CV	4" Pop-Up w/Check Valve
	I-PRO400-PR	4" Pop-Up w/Pressure Regulator
	I-PRO400-PR-CV	4" Pop-Up w/Pressure Regulator and Check Valve
\succ	I-PRO600	6″Pop-Up
ворү	I-PRO600-CV	6" Pop-Up w/Check Valve
BO	I-PRO600-PR	6" Pop-Up w/Pressure Regulator
	I-PRO600-PR-CV	6" Pop-Up w/Pressure Regulator and Check Valve
FULL	I-PRO600-SI	6" Pop-Up w/Side Inlet
Ľ	I-PRO600-SI-PR	6" Pop-Up w/Side Inlet and Pressure Regulator
	I-PRO1200-SI	12" Pop-Up w/Side Inlet
	I-PRO1200-SI-CV	12" Pop-Up w/Side Inlet and Check Valve
	I-PRO1200-SI-PR	12" Pop-Up w/Side Inlet and Pressure Regulator
	- I-PRO1200-SI-PR-CV	12" Pop-Up w/Side Inlet, Pressure Regulator and Check Valve
	- I-PRO400R	4" Pop-Up Replacement
	I-PRO400R-CV	4" Pop-Up Replacement w/Check Valve
	I-PRO400R-PR	4" Pop-Up Replacement w/Pressure Regulator
_	I-PRO400R-PR-CV	4" Pop-Up Replacement w/Pressure Regulator and Check Valve
<u> </u>	I-PRO600R	6" Pop-Up Replacement
RETROFIT	I-PRO600R-CV	6" Pop-Up Replacement w/Check Valve
	I-PRO600R-PR	6" Pop-Up Replacement w/Pressure Regulator
	I-PRO600R-PR-CV	6" Pop-Up Replacement w/Pressure Regulator and Check Valve
	I-PRO1200R	12" Pop-Up Replacement
	I-PRO1200R-CV	12" Pop-Up Replacement w/Check Valve
	I-PRO1200R-PR	12" Pop-Up Replacement w/Pressure Regulator
	I-PRO1200R-PR-CV	12" Pop-Up Replacement w/Pressure Regulator and Check Valve

REPLACEMENT SPRAY AVAILABLE (4", 6" & 12")

Why pay for a body you're just going to throw away? I-PRO offers a 4", 6" and 12" replacement spray head that is everything but the body! Ideal for maintenance, this spray head also fits right in the can of the Rain Bird[®] 1800[®] series for an easy retrofit. With features that are contractor-driven and field-proven, the I-PRO Series is sure to save you time and money.



Easily retrofits to Rain Bird 1800 Series



Rain Bird 1806 spray head

Drop in I-PRO replacement and retrofit is complete



Pressure-activated lip seal ensures a positive seal around the riser and reduces "flow-by"

Lip creates positive seal to prevent body to cap leaks

We reserve the right to improve our products and make changes in the specifications and designs without notice and without incurring obligation. Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary in design and features.

